

# Product Data Sheet

## Weathercoat All Guard XP advance

### DESCRIPTION

Weather coat all guard XP advance is high performance premium exterior emulsion paint with high sheen. It is formulated with a special grade of acrylic emulsion with light fast pigments and special additives. This ensures long term protection of the surface and preserves its rich new look. It is resistant to chalking, flaking, fading etc. and prevents fungi & algae growth for long time.

### AREAS OF APPLICATION

Weathercoat all guard XP advance is suitable for sand/cement plaster surface, concrete, asbestos etc.

*Note: This product is not recommended on lime wash.*

### APPLICATION TOOLS

Brush, roller and conventional spray.

### RECOMMENDED DILUTION

40% by volume.

### APPLICATION DETAILS

- **Surface preparation**

For new masonry, it should be allowed to cure completely. One coat of illusion sealer is recommended to avoid problem of salt petering. For old surface, ensure the surface is free from loose paints, dust, grease, fungus, algae etc. by sanding or wire brushing. Cracks, holes, dents, damp areas etc. should be repaired properly before painting. Treat the surface with Biowash solution and wash it next day with potable water and let the surface to dry completely.

- **Priming** : Apply 1-2 coats of WC Seal-O-Prime (for better performance) or WC Exterior Primer.
- **Top coat**: Apply 2-3 coats of top coat with 4-6 hours of interval.

### TECHNICAL DATA

Drying time: Surface dry = 30 minutes; Hard dry = 4-6 hours

Gloss at 60° GH: 10-15

Dilution: 40% by volume with water. For dark shades 0-10%

Pot life of thinned material: Within 24 hours

Application Method: Brush, roller, spray

Over coating interval: 4-6 hours

Coverage: 60-70 sq. ft./Lit/2 coats depending upon the conditions of the substrate and shade.

### PRECAUTIONS

- Stir and strain the diluted paint well before use
- Do not over dilute or over extend brush.
- Do not apply paint on high alkaline surface.
- Do not apply paint on wet surface.
- Do not apply paint on chalking or flaking surface or where the surface is infected with fungus or algae.

- Do not apply paint if the ambient temperature is less than or expected to fall below 10°C.
- Use only Berger Paints' machine colorants to tint shades
- Allow sufficient time for each coat to dry before next coat application.

**SAFETY DATA**

Refer MSDS